WELL MASTER
Produce more. Spend less.

Hawkeye XP
Plunger Arrival Sensor

The Hawkeye XP Plunger Arrival Sensor

EXPLOSION PROOF WITH SELF CALIBRATION

APPLICATIONS

Designed for reliable operation in extreme conditions

FEATURES AND BENEFITS

- ***Adjustable sensitivity levels*** allows for utmost accuracy
- Extremely ***low power consumption,*** drawing less than 700 µA of current
- Does not use internal batteries
- Protected by a ***rugged water-resistant*** aluminum explosion proof encloser
- Features a ***1/2" NPT port*** that enables use of either a Teck connector & armored cable or a standard cable gland & instrumentation cable
- Detects plunger arrivals from ***up to three feet away***

TECHNICAL SPECIFICATIONS

Part No.	CONX010SETCX
Operating Temp.	-40°F to +158°F (-40°C to +70°C)
Operating Valve	5V to 28V
Average Current	<700 µA
Interface	3 Wire (COM/SIG/PWR)
Operating Mode	Normally Open
Certifications	Class 1, Zone 0, Ex ia IIB T4 Class 1, Zone 0, AEx ia IIB T4
Mounting	Stainless steel clamp Mounts to pipes up to 3.5" diameter

Contact Well Master today to find out how we can help optimize your oil and gas well production.

Call **303.980.0254** | Email **info@wellmaster.com** | Visit **www.wellmaster.com**.
16201 Table Mountain Parkway, Suite 100 | Golden, CO 80403 | Fax: 303.980.0355

©2021 Well Master Corporation, all rights reserved