



WELL MASTER

Produce more. Spend less.

MODEL 550

ECONOMICAL PLUNGER LIFT CONTROLLER WITH PRESSURE OVERRIDE

APPLICATIONS

Designed to withstand extreme conditions for plunger lift system control.

FEATURES AND BENEFITS

- **Proven to function reliably** in temperatures as low as -20°F and up to 158°F
- Draws little energy from rechargeable battery, **operating for more than 3+ months** on a single charge from the solar panel
- Protected by a **rugged water-tight** steel encloser with a locking door latch
- **Features several pre-punched ports** to provide a variety of options for solenoid and wiring connector locations
- Can be configured as a simple well intermittent or used in conjunction with a plunger arrival sensor **to optimize production**



CON5500

TECHNICAL SPECIFICATIONS

| | |
|-------------------------|------------------------------------|
| Part No. | CON5500 |
| Operating Temp. | -20°F to +158°F |
| Battery | 6 V, 4.5 Ah |
| Solar Panel | 6V, 1.1 W |
| Standby Time | 3+ Months |
| Valves Supported | 1/1 |
| Arrival Sensor | Well Master Plunger Arrival Sensor |
| Cycle History | Last 25 Plunger Cycles |

Contact Well Master today to find out how we can help optimize your oil and gas well production.

Call **303.980.0254** | Email info@wellmaster.com | Visit www.wellmaster.com
16201 Table Mountain Parkway, Suite 100 | Golden, CO 80403 | Fax 303.980.0355

©2023 Well Master Corporation, All rights reserved.