



WELL MASTER

Produce more. Spend less.



HORIZONTAL SPRING

THE HORIZONTAL SPRING THAT INCREASES PRODUCTION THROUGH A WIDER SET RANGE



SPR2000AHZS23XP60

APPLICATIONS

Engineered specifically for **HORIZONTAL WELLS** that can be set deeper and assist in increasing production and deliquifications

FEATURES AND BENEFITS

- **HIGH RANGE** of setting angles from 0° to 68° from vertical
- **INCREASED GAS PRODUCTION** due to a more efficient liquid removal design and an ability to reduce bottom hole pressure
- **LARGER FLOW THROUGH AREA** of 56% that allows for higher flow rates and less back pressure
- **CUSTOMIZABLE** to a variety of hold down methods including seating nipples, collar stops, tubing stops, and swab cups
- **HEAT-RESISTANT** and standard fiber seat cups to prevent bumper spring from moving out of position (2 or 3 cup configurations)
- **AVAILABLE** in many fluid retention options including standing valve (STV) or multiple pressure relieving ratings (SPR)



WELL MASTER
Produce more. Spend less.



HORIZONTAL SPRING

TECHNICAL SPECIFICATIONS

Part Family	Outside Tubing Dia. (in.)	Nominal Inside Tubing Dia. (in.)	Nominal Tubing Weight (lbs./ft.)	Tool Length (in.)	Nominal Tool Dia. (in.)	Tool Weight (lbs.)	Seat Cups
STANDING VALVE SPRING ASSEMBLY WITH PRESSURE RELIEF							
SPR2000ALM	2 3/8	1.995	4.70	23.32	1.900	9.0	Yes
STANDING VALVE SPRING ASSEMBLY							
STV2000ALM	2 3/8	1.995	4.70	22.93	1.900	9.0	Yes
STV2500ALM	2 7/8	2.441	6.50	22.5	2.320	15.0	Yes
STOP WITH VALVE ASSEMBLY							
SWV2000ALM	2 3/8	1.995	4.70	13.79	1.900	5.0	Yes
STOP ASSEMBLY							
STP2000ALM	2 3/8	1.995	4.70	13.70	1.900	4.0	Yes
SEAT CUP SPRING ASSEMBLY							
SCS1500ALM	1 1/2	1.650	2.40	19.50	1.500	6.0	Yes
SCS1700ALM	2 1/16	1.751	3.25	19.50	1.700	6.2	Yes
SCS2000ALM	2 3/8	1.995	4.70	22.50	1.900	8.6	Yes
SCS2500ALM	2 7/8	2.441	6.50	22.50	2.320	15.0	Yes
COLLAR STOP SPRING ASSEMBLY							
SCS2000FLM	2 3/8	1.995	4.70	27.25	1.735	9.0	N/A
SCS2500FLM	2 7/8	2.441	6.50	27.25	2.320	15.0	N/A
COLLET SPRING ASSEMBLY							
SCS2000CLM	2 3/8	1.995	4.70	21.67	1.900	7.0	N/A
TUBING STOP SPRING ASSEMBLY							
SCS2000BLM	2 3/8	1.995	4.70	30.25	1.735	10.0	N/A
SCS2500BLM	2 7/8	2.441	6.50	30.25	2.320	16.0	N/A
Materials of Construction:	Body: Standard construction 4140 steel; Alternate construction available in 17-4SS stainless steel or grade 5 Titanium Spring: Standard carbon steel spring or 304SS Cups: Standard fiber seal cups; High temperature composite also available						

Contact Well Master today to find out how we can help optimize your oil and gas well production.

Call 303.980.0254 | Email info@wellmaster.com | Visit www.wellmaster.com
 16201 Table Mountain Parkway, Suite 100 | Golden, CO 80403 | Fax 303.980.0355

©2023 Well Master Corporation, All rights reserved.