



**DURABLE, LOW MAINTENANCE, ECONOMICAL SOLID PLUNGER**

**APPLICATIONS**

- Designed for wells with **deviated tubing**
- Effective against **paraffin, salt, and scale producing wells**
- Used in **high liquid producing wells**

**FEATURES AND BENEFITS**

- **Spin-cleaning** flutes work on cutting debris during plunger downstroke, extending the life of the plunger and reducing wear
- Variable groove depth and spin turbulence **increases sealing efficiency**
- Hardened solid plunger with grooves designed to remove liquids in wells with moderate to high gas volumes
- Uniquely crafted from hardened steel and plated with electroless nickel providing **superior durability**, extending the time between replacements, increasing your wells' profits and productivity



PLS2000SW

**TECHNICAL SPECIFICATIONS**

Part No.	Outside Tubing Dia. (in.)	Nominal Inside Tubing Dia. (in.)	Nominal Tubing Weight (lbs./ft.)	Plunger Length (in.)	Nominal Plunger Dia. (in.)	Plunger Weight (lbs.)
PLS1250SW	1 3/5	1.380	2.33	9.60	1.265	2.5
PLS1500SW	1 9/10	1.650	2.36	9.30	1.500	3.2
PLS1500SWL	1 9/10	1.650	2.36	12.57	1.500	4.5
PLS1700SW	2 1/16	1.751	3.25	10.60	1.641	3.8
PLS1700SWL	2 1/16	1.751	3.25	13.13	1.646	5.6
PLS2000SW*	2 3/8	1.995	4.70	10.60	1.900	6.1
PLS2000SWL	2 3/8	1.995	4.70	15.00	1.900	8.9
PLS2500SW*	2 7/8	2.441	6.50	10.60	2.335	10.0
PLS2500SWL	2 7/8	2.441	6.50	15.35	2.335	13.9
<b>Materials of Construction:</b>	Constructed of hardened and electroless nickel plated steel for sweet gas service *Available in stainless steel options Sour Gas: Treated <b>stainless steel</b> for corrosive environments- Add H2S to the end of part number					

**Contact Well Master today to find out how we can help optimize your oil and gas well production.**

Call **303.980.0254** | Email [info@wellmaster.com](mailto:info@wellmaster.com) | Visit [www.wellmaster.com](http://www.wellmaster.com)  
16201 Table Mountain Parkway, Suite 100 | Golden, CO 80403 | Fax 303.980.0355